Water Pipe and Water Heater Freeze Prevention

Equipment malfunctions due to freezing are more likely to occur during the winter season.

Be sure to drain the water in the following situations!

- Before going to bed (when the forecast low temperature is -4°C or below)
- On days when the temperature remains below 0°C throughout the day
- During long absences (returning home, travel, business trips, etc.)


Important Notice
Repair costs may be charged if freezing damage is caused by failure to drain the water or improper operation.

Precautions to Prevent Freezing

- ☐ Do not unplug the water heater power cord.
- ☐ Leave the heated bidet toilet seat powered ON.
- ☐ Do not turn off the circuit breaker.
- ☐ Leave water in the toilet bowl and drain the tank if necessary.

Water Draining Procedure

① Close the main water valve.



Turn clockwise (to the right) to close.

② Open the water heater drain valve.




Turn counterclockwise (to the left) to open.

③ Open the faucets in the kitchen, washbasin and bathroom.



Open slightly and let the water flow.

④ Open the drain valves for the water supply and hot water pipes.



Turn counterclockwise (to the left) to open.

⑤ Drain the water from the bathtub and toilet.



Remove the plug and drain all the water.

⑥ Operate the reheating function from the control panel

※Only if the equipment is installed.



Remove the plug and drain all the water.


⑦ Once drainage stops, the procedure is complete. Leave the main water valve closed.



Water Draining Complete

Leave the main water valve closed.

⑧ Close all valves and faucets that were opened during the draining process.



Turn clockwise (to the right) to close.